

# AMPLIFIED INDUCTIVE SENSORS



IS Series




Ø 8

10÷30 V DC - 3 WIRES NPN OR PNP OUTPUT

- Range, 1,5mm to 2mm - shielded, not shielded
- Short housing models
- Cable or M8 and M12 quick connect models
- Operation LED
- Stainless steel housing

## IDENTIFICATION CODE




(1) Available only on short housing configuration.  
 (2) Available only on short stainless steel housing.


	SHIELDED	NOT SHIELDED
NOMINAL SWITCHING DISTANCE (Sn)	1,5 mm	2 mm
NOMINAL VOLTAGE	10 ÷ 30 VDC (-15 / +10%)	
RESIDUAL RIPPLE	≤ 10%	
HYSTERESIS	< 10%	
MAX. OUTPUT CURRENT	200 mA	
RESIDUAL CURRENT	< 10 mA	
VOLTAGE DROP (Sensor ON)	< 1.2 V (I = 100 mA)	
OPERATION LED	Yellow	
SWITCHING FREQUENCY	1000 Hz	
START UP DELAY	≤ 50 ms	
REPEATABILITY	≤ 3%	
SHORT CIRCUIT PROTECTION	Present (self-resetting)	
ELECTRIC PROTECTIONS	Against polarity reversal - inductive loads	
TEMPERATURE LIMITS	- 25 ÷ +70 °C	
PROTECTION DEGREE	IP 67	
CABLE LENGTH	2 m	
CABLE SECTION	3 x 0,14 mm <sup>2</sup>	
HOUSING MATERIAL	Nickel-plated brass	
WEIGHT - Cable output -	80 g	
WEIGHT - K1 connector output -	40 g	
WEIGHT - K connector output -	55 g	

<sup>(3)</sup> Device marking II 3D IP67 T6X.

## WIRING DIAGRAMS



## CONNECTION WITH CONNECTOR M12 (K)




View of quadripole male connector

### CONTACTS CONFIGURATION

Available	Contacts numbers			
	1	2	3	4
(NO or NC)	+		-	NO/NC

## CONNECTION WITH CONNECTOR M8 (K1)




View of tripole male connector

### CONTACTS CONFIGURATION

Available	Contacts numbers		
	1	3	4
(NO or NC)	+	-	NO/NC

## DIMENSIONS (mm)



(\* The dimensions into brackets refer to short housing models

**Note:** the front part in blue refers to not shielded models