





















M8**Tubular Inductive Proximity Sensor****◆Specifications / 規格表 :**

SCS0801-□  38.5		 M8 0.5 4 SCS:36 SC:50 LED Ø3 2M Cable		 M8 0.5 4 SCS:36 SC:50 LED Ø4 15cm Cable M8 x 1.0 25 6		 M8 3 4 SCS:33 SC:47 LED Ø3 2M Cable		 M8 3 4 SCS:33 SC:47 LED Ø4 15cm Cable M8 x 1.0 25 6	
SC0801-□D  52.5		 14.8 12.8 <unit:mm>		 4 OUT +1 3- 14.8 12.8 <unit:mm>		 14.8 12.8 <unit:mm>		 4 OUT +1 3- 14.8 12.8 <unit:mm>	
SCS0802-□  38		 14.8 12.8 <unit:mm>		 4 OUT +1 3- 14.8 12.8 <unit:mm>		 14.8 12.8 <unit:mm>		 4 OUT +1 3- 14.8 12.8 <unit:mm>	
SC0802-□  52 <unit:mm>		 14.8 12.8 <unit:mm>		 4 OUT +1 3- 14.8 12.8 <unit:mm>		 14.8 12.8 <unit:mm>		 4 OUT +1 3- 14.8 12.8 <unit:mm>	
Output method / 輸出模式	NPN N.O.	SC□0801-N	SC□0801-ND	SC□0802-N	SC□0802-ND				
	NPN N.C.	SC□0801-N2	SC□0801-N2D	SC□0802-N2	SC□0802-N2D				
	PNP N.O.	SC□0801-P	SC□0801-PD	SC□0802-P	SC□0802-PD				
	PNP N.C.	SC□0801-P2	SC□0801-P2D	SC□0802-P2	SC□0802-P2D				
	NPN N.O./N.C. PNP N.O./N.C.	-	-	-	-				
	SCR N.O.	-	-	-	-				
	SCR N.C.	-	-	-	-				
Sensing type / 檢出方式	Shielded / 隔離型			Unshielded / 非隔離型					
Description / 外型	Standard / 標準M8								
Standard sensing object / 標準檢測物	Iron 8 x 8 x 1 mm								
Sensing distance / 檢出距離	1 mm			2 mm					
Secure sensing distance / 建議距離	0 to 0.8 mm			0 to 1.6 mm					
Hysteresis / 遲滯	≤ 10 % of sensing distance								
Response time / 反應時間	1 ms Max.								
Operating voltage / 工作電壓	DC12 ~ 24 V								
Current consumption / 消耗電流	≤ 8 mA no-load								
Load current / 負載電流	100 mA Max at DC 24V								
Leakage current / 漏電流	≤ 1.1 mA no-load								
Residual voltage / 殘餘電壓	≤ DC 1.5V								
Insulation resistance / 隔離阻抗	20MΩ min. (DC500V)								
Voltage withstandability / 絕緣耐壓	AC1000V 60Hz for 60 Sec.								
Operating temperature / 工作溫度	-20°C ~ + 60°C								
Protection degree / 防水等級	IP 66								
Wiring method / 出線方式	Pre-wired Ø3 x 2M / 3-wires	M8 pigtailed type / M8接頭15cm電線式	Pre-wired Ø3 x 2M / 3-wires	M8 pigtailed type / M8接頭15cm電線式					
Weight / 重量	Approx.30g	Approx.12g	Approx.30g	Approx.12g					

AUTEK Ltda.

www.autek.cl 02-5113684 ventas@autek.cl

RIKO