

DC STANDARD BODY WITH EXTENDED SENSING DISTANCE PROXIMITY SWITCH

M12		
●	○	
4 mm	8mm	
nickel plated brass		
●		
10-30VDC		
<10%		
<10mA		
200mA		
<0.01mA		
-		
-		
<1.5V		
2KHZ	1KHZ	
0.1ms/0.1ms	0.2ms/0.2ms	
<15%		
<1.0%(Sr)		
IP67		
-25 °C - +70 °C		
<10%(Sr)		
YES		
220mA		
<10ms		
RFI>3V/m / EFT>1KV / ESD>4KV (contact)		
IEC 60947-5-2,Part 7.4.1 / IEC 60947-5-2,Part 7.4.2		
POM	PBT	
ECM1-1204N-A3U2	1	ECM2-1208N-A3U2
ECM1-1204N-B3U2	2	ECM2-1208N-B3U2
ECM1-1204P-A3U2	3	ECM2-1208P-A3U2
ECM1-1204P-B3U2	4	ECM2-1208P-B3U2
ECM1-1204P-S4U2	6	ECM2-1208P-S4U2
ECM1-1204N-S4U2	5	ECM2-1208N-S4U2
ECM1-1204C-A2U2	7	ECM2-1208C-A2U2
ECM1-1204C-B2U2	8	ECM2-1208C-B2U2
4φ 3x0.34		
Approx.67 g	Approx.67 g	

DC STANDARD BODY WITH EXTENDED SENSING DISTANCE PROXIMITY SWITCH