

DC STANDARD BODY WITH EXTENDED SENSING DISTANCE PROXIMITY SWITCH

M18		
●	○	
8 mm	16 mm	
nickel plated brass		
●		
10-30VDC		
<10%		
<10mA		
200mA		
<0.01mA		
-		
-		
<1.5V		
500HZ	150HZ	
0.5ms/0.5ms	1ms/1ms	
<15%		
<1.0%(Sr)		
IP67		
-25 °C - +70 °C		
<10%(Sr)		
YES		
220mA		
<10ms		
RFI>3V/m / EFT>1KV / ESD>4KV (contact)		
IEC 60947-5-2,Part 7.4.1 / IEC 60947-5-2,Part 7.4.2		
PBT		
ECM1-1808N-A3U2	1	ECM2-1816N-A3U2
ECM1-1808N-B3U2	2	ECM2-1816N-B3U2
ECM1-1808P-A3U2	3	ECM2-1816P-A3U2
ECM1-1808P-B3U2	4	ECM2-1816P-B3U2
ECM1-1808P-S4U2	6	ECM2-1816P-S4U2
ECM1-1808N-S4U2	5	ECM2-1816N-S4U2
ECM1-1808C-A2U2	7	ECM2-1816C-A2U2
ECM1-1808C-B2U2	8	ECM2-1816C-B2U2
5.0 ϕ 44x0.1		
Approx.153 g	Approx.144 g	