




SRD-PK3DU30P, SRD-PK3DU30PD, SRR-PK3R2P.

◆ Shape/外觀:			
◆ Specifications /規格表:			
Catalog Listing / 型號	PK3-DU30N PK3-DU30P	PK3-R2N PK3-R2P	PK3-5N PK3-5P
	PK3-DU30ND PK3-DU30PD	PK3-R2ND PK3-R2PD	PK3-5ND PK3-5PD
Description / 檢出方式	Diffuse reflection / 擴散反射式	Retro reflection/ 鏡片反射式	Through beam / 對照式
Sensing distance / 檢出距離	30 cm	2M	5M
Output method / 輸出模式	NPN.NO / PNP.NO		
Response time / 反應時間	1.5 ms Max.		
Light emitter / 發光源	850 nm.	940 nm.	850 nm.
Operating voltage / 工作電壓	DC: 12 ~ 24 VDC		
Current consumption / 消耗電流	25 mA Max.		40 mA Max.
Output current / 輸出電流	24 VDC 100mA max.		
Insulation resistance / 隔離阻抗	20M Ω Min. 500VDC		
Dielectric strength / 絕緣耐壓	1000VAC for 1min.		
Ambient humidity / 工作溼度範圍	35%~85% RH		
Weight / 重量	Approx 60g		
Operating temperature/工作溫度範圍	- 20 °C ~ + 60 °C		
Housing material / 外觀材質	ABS		
Wiring method / 出線方式	PK3-□N/P: Ø4 × 2 M / 3-cores PK3-□D: M8 pigtailed type/M8 接頭15cm 電線式		
Protection degree / 防水等級	IP65		
◆ Dimensions /尺寸圖:	